

(19) World Intellectual Property
Organization
International Bureau



(43) International Publication Date
5 August 2004 (05.08.2004)

PCT

(10) International Publication Number
WO 2004/065078 A1

(51) International Patent Classification⁷: B26B 19/14,
19/28

(21) International Application Number:
PCT/IB2004/050001

(22) International Filing Date: 12 January 2004 (12.01.2004)

(25) Filing Language: English

(26) Publication Language: English

(30) Priority Data:
03100098.7 20 January 2003 (20.01.2003) EP

(71) Applicant (for all designated States except US): KONIN-
KLIJKE PHILIPS ELECTRONICS N.V. [NL/NL];
Groenewoudseweg 1, NL-5621 BA Eindhoven (NL).

(72) Inventors; and

(75) Inventors/Applicants (for US only): BARON, Sint


[NL/NL]; c/o Prof. Holstlaan 6, NL-5656 AA Eind-
hoven (NL). KLOKMAN, Pieter, H. [NL/NL]; c/o Prof.
Holstlaan 6, NL-5656 AA Eindhoven (NL). KALMA,
Bauke [NL/NL]; c/o Prof. Holstlaan 6, NL-5656 AA
Eindhoven (NL). WESTRA, Thewis, M. [NL/NL]; c/o
Prof. Holstlaan 6, NL-5656 AA Eindhoven (NL).

(74) Agent: BOS, Kornelis, S.; Prof. Holstlaan 6, NL-5656
AA Eindhoven (NL).

(81) Designated States (unless otherwise indicated, for every
kind of national protection available): AE, AG, AL, AM,
AT, AU, AZ, BA, BB, BG, BR, BW, BY, BZ, CA, CH, CN,
CO, CR, CU, CZ, DE, DK, DM, DZ, EC, EE, EG, ES, FI,
GB, GD, GE, GH, GM, HR, HU, ID, IL, IN, IS, JP, KE,
KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MA, MD,
MG, MK, MN, MW, MX, MZ, NA, NI, NO, NZ, OM, PG,
PH, PL, PT, RO, RU, SC, SD, SE, SG, SK, SL, SY, TJ, TM,
TN, TR, TT, TZ, UA, UG, US, UZ, VC, VN, YU, ZA, ZM,
ZW.

[Continued on next page]

(54) Title: SHAVING APPARATUS



(57) Abstract: A shaving apparatus has plurality of shaving heads, each with a rotatable cutting member (5) associated with and rotatable relative to a shear plate (3). For driving the cutting members (5), a plurality of drive units (9) is provided, each of said units extending at least from drive rim (7) engaged for driving the drive unit to a coupling end (27) coupled to one of the cutting members (5) for transmitting a rotation of the drive unit (9) to the cutting member (5). The drive rims (7) of the drive units (9) are suspended for rotation about axes of rotation (20) that are oriented at angles relative to each other and diverge from each other in a direction from the drive rim (7) to the coupling (27).

WO 2004/065078 A1